


リング式銅管継手(計装用)
バルクヘッドメスユニオン


型 式	銅管外径		管径ねじ		本体長さ		最小穴径	差込深さ		対 辺	
	A (mm)	B (Rc)	L1 (mm)	L2 (mm)	d (mm)	φ1 (mm)	φ2 (mm)	H1 (mm)	H2 (mm)		
GBC-5101R-BS	6	1/8	28	8	5	7	9.5	32	14		
GBC-5102R-BS	6	1/4	28	8	5	7	9.5	32	14		
GBC-5103R-BS	6	3/8	40	20	5	7	9.5	32	14		
GBC-5104R-BS	6	1/2	45	25	5	7	9.5	32	14		
GBC-5201R-BS	8	1/8	28	8	6	7	9.5	32	14		
GBC-5202R-BS	8	1/4	28	8	6	7	9.5	32	14		
GBC-5203R-BS	8	3/8	40	20	6	7	9.5	32	14		
GBC-5204R-BS	8	1/2	45	25	6	7	9.5	32	14		
GBC-5301R-BS	10	1/8	29	8	8	7	11	32	17		
GBC-5302R-BS	10	1/4	29	8	8	7	11	32	17		
GBC-5303R-BS	10	3/8	41	20	8	7	11	32	17		
GBC-5304R-BS	10	1/2	46	25	8	7	11	32	17		
GBC-5401R-BS	12	1/8	30	8	8	7	12	32	19		
GBC-5402R-BS	12	1/4	30	8	10	7	12	32	19		
GBC-5403R-BS	12	3/8	42	20	10	7	12	32	19		
GBC-5404R-BS	12	1/2	47	25	10	7	12	32	19		
GBC-5021R-BS	6.35	1/8	28	8	5	7	9.5	32	14		
GBC-5022R-BS	6.35	1/4	28	8	5	7	9.5	32	14		
GBC-5023R-BS	6.35	3/8	40	20	5	7	9.5	32	14		
GBC-5024R-BS	6.35	1/2	45	25	5	7	9.5	32	14		
GBC-5031R-BS	9.53	1/8	29	8	8	7	11	32	17		
GBC-5032R-BS	9.53	1/4	29	8	8	7	11	32	17		
GBC-5033R-BS	9.53	3/8	41	20	8	7	11	32	17		
GBC-5034R-BS	9.53	1/2	46	25	8	7	11	32	17		
GBC-5041R-BS	12.7	1/8	33	8	8	8	12.5	32	21		
GBC-5042R-BS	12.7	1/4	33	8	10	8	12.5	32	21		
GBC-5043R-BS	12.7	3/8	45	20	10	8	12.5	32	21		
GBC-5044R-BS	12.7	1/2	50	25	10	8	12.5	32	21		

※貫通穴は全サイズ共通φ21mm